

E-Z-GO® EXPRESS™ L6

LET THE GOOD TIMES GROW.

It's time to get away, time to explore and see what adventures you can find along the next path. With eco-friendly powertrain options, rugged tires, and higher ground clearance, the Express L6 gives you a smooth and stylish ride. Whether it's camping with the family or exploring a new trail with friends, let the Express L6 take you there.

STANDARD FEATURES

- ▶ 23-in all-terrain tires
- Alloy wheels
- Front brush guard
- ► Headlights, taillights and brake lights
- ► Fold down cargo deck
- Cupholders
- Dashboard storage pockets
- ► Low oil indicator (gas only)
- Fuel gauge (gas only)
- State of charge meter (electric only)



www.ezgo.com

ELECTRIC

Overall Length Overall Width Overall Height (w/o roof) Overall Height (w/ roof) Wheel Base Front Wheel Track Rear Wheel Track

Ground Clearance @ Differential

POWER

DIMENSIONS

Power Source Valve Train Motor Type Horsepower (kW) Electrical System Batteries (qty/type) Key or Pedal Start Air Cleaner Lubrication Oil Filter Cooling System Fuel Capacity Battery Charger Speed Controller Drivetrain Transaxle Gear Selection Rear Axle Ratio PERFORMANCE Seating Capacity Dry Weight (w/o batteries) Curb Weight Vehicle Load Capacity Outside Clearance Circle Intersecting Aisle Clearance Speed (level ground) **STEERING & SUSPENSION** Steering Suspension Service Brake Parking Brake Tires **BODY & CHASSIS** Frame Body & Finish Available Body Colors

> Standard Seat Color Optional Seat Colors

143.5 in (364 cm)	143.5 in (364 cm)
49.0 in (125 cm)	49.0 in (125 cm)
52.5 in (133 cm)	53.5 in (136 cm)
77.5 in (197 cm)	78.5 in (200 cm)
96.5 in (245 cm)	94.5 in (240 cm)
38.5 in (98 cm)	38.5 in (98 cm)
39.0 in (99 cm)	39.0 in (99 cm)
7.0 in (18 cm)	6.0 in (15 cm)
48 Volt DC	4-Cycle 24.5 cu in (401cc) Low-Emissions
N/A	Single Cylinder OHV
Shunt Wound	N/A
 N/A	13.5 hp (10.1 kW) Exceeds SAE J1940 Std
48 Volt	Starter/Generator — Solid State Regulator
Eight, 6 Volt Deep Cycle	One, 12 Volt Maintenance Free
Pedal	Pedal
N/A	Replaceable Dry Cartridge
N/A	Pressurized Oil System
N/A	Spin-On
N/A	Air Cooled
N/A	5.8 Gallon (22.0 L)
48V DC, 120/230 VAC, UL & CSA	N/A
400 Amp	N/A
Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
Differential with Helical Gears	Differential with Helical Gears
Dash Mounted Forward-Neutral-Reverse	Forward-Reverse
14.7:1	11.42:1 (Forward), 15.78:1 (Reverse)
6-Passenger (4-Passenger with Optional Cargo Bed)	6-Passenger (4-Passenger with Optional Cargo Bed)
974 lb (442 kg)	1,063 lb (482 kg)
1,470 lb (667 kg)	1,110 lb (504 kg)
1,200 lb (540 kg)	1,200 lb (540 kg)
25.5 ft (7.8 m)	25.5 ft (7.8 m)
6.5 ft (1.98 m)	6.5 ft (1.98 m)
16.0 mph \pm 0.5 mph (26.0 kph \pm 0.8 kph)	16.0 mph \pm 0.5 mph (25.7 kph \pm 0.8 kph)
Self-Compensating Reduction Rack and Pinion	Self-Compensating Reduction Rack and Pinion
Leaf Springs with Hydraulic Shock Absorbers	Leaf Springs with Hydraulic Shock Absorbers
Rear Wheel Mechanical Self-Adjusting Drum	Rear Wheel Mechanical Self-Adjusting Drum
Self-Compensating, Single Point Engagement	Self-Compensating, Single Point Engagement
All-Terrain 23x10.5-12, Alloy Wheel	All-Terrain 23x10.5-12, Alloy Wheel
Welded Steel with DuraShield™ Powder Coat	Welded Steel with DuraShield™ Powder Coat
Injection Molded TPO	Injection Molded TPO
Almond, Black, Burgundy, Electric Blue, Flame Red, Forest	Almond, Black, Burgundy, Electric Blue, Flame Red, Forest
Green, Inferno Red, Ivory, Metallic Charcoal, Orange, Patriot Blue, Platinum, White	Green, Inferno Red, Ivory, Metallic Charcoal, Orange, Patriot Blue, Platinum, White
Red on Black	Red on Black
Black, Oyster, Tan, Brown, Gray on Black, White on Blue, White on Red	Black, Oyster, Tan, Brown, Gray on Black, White on Blue, White on Red

GAS



FRONT



BACK

POPULAR OPTIONS & ACCESSORIES

- ► Fold-down windshield
- ▶ Roof
- ▶ Woodside stake cargo bed (replaces rear-facing seat)
- ▶ Roto-molded plastic bed (replaces rear-facing seat)
- Comfort grip steering wheel
- ▶ High-output LED headlights
- ▶ Turn signals w/ 4-way flashers
- Hour meter
- ▶ Limited slip differential ▶ Clays Car[™] field kit
- ▶ 2-in (5 cm) front hitch receiver
- ▶ Rear fender flares
- Ashtray
- ► CE kit (gas only)
- ▶ 12-volt accessory outlet (gas only) DC/DC converter (electric only)
- Battery watering system (electric only)

